

IN THE SPECIFICATION

Please amend page 17, as follows:

ABSTRACT

The present invention relates to a commodity package, comprising a hanging member that has a hole for hanging, and a holding body for holding an article. The holding body has a first cutting portion for separating a first recess and the upper part of a first brim portion from each other, and a second cutting portion for separating a second recess and the upper part of a second brim portion from each other. The hanging member has a third cutting portion for separating the upper part and the lower part thereof from each other. The first, second and third cutting portions are provided at different heights.

This makes it possible for the commodity package, when hung, to maintain favorable balance and obtain sufficient intensity.

The present invention relates to a commodity package, comprising a hanging member that has a hole for hanging, and a holding body for holding an article. The holding body has a first cutting portion for separating a first recess and the upper part of a first brim portion from each other, and a second cutting portion for separating a second recess and the upper part of a second brim portion from each other. The hanging member has a third cutting portion for separating the upper part and the lower part thereof from each other. The first, second and third cutting portions are provided at different heights. This makes it possible for the commodity package, when hung, to maintain favorable balance and obtain sufficient intensity.

Please amend page 7, lines 11 to 26 as follows:

The holding body 8 has a first cutting portion 20 comprising a breaking line for separating the first brim portion 9 and the first recess 11 from each other, and a second cutting portion 21 comprising a breaking line for separating the second brim portion 10 and the second recess 12 from each other. Further, the hanging member 3 has a third cutting portion 6 comprising a breaking line for separating the upper part 3a and the under part 3c from each other. As in FIG. 1 and FIG. 8 that shows the battery package after the opening thereof, the first cutting portion ~~[[6]]~~ 20, the second cutting portion ~~[[20]]~~ 21 and the third cutting portion ~~[[21]]~~ 6 are provided at different heights when a battery package is constituted by folding back the holding body 8 to sandwich the hanging member 3. The provision of the respective cutting portions at different heights enables improvement in intensity of the battery package when hung for exhibition.